

Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

EP 1 035 509 A1

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:  
13.09.2000 Bulletin 2000/37

(51) Int Cl.7: G06T 7/00, G06T 5/00

(21) Application number: 99125092.9

(22) Date of filing: 16.12.1999

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(71) Applicant: Hyundai Motor Company  
Seoul (KR)

(72) Inventor: Byoung-Soo, Kim  
Ansan-si, Kyungki-do (KR)

(30) Priority: 12.03.1999 KR 9908274


(74) Representative: Viering, Jentschura & Partner  
Postfach 22 14 43  
80504 München (DE)

### (54) Road modeling method for lane drifting warning system

(57) Disclosed is a road modeling method for a lane drifting system. The method includes the steps of extracting an edge of lane markers of a lane in which a vehicle is being driven by a camera collecting images of the lane markers and outputting corresponding image signals, removing noise from the lane marker image signals, and dividing the image signals into multiple resolutions; performing road modeling by inputting a minimum number of possible marking points of lane edges, and extracting two straight lines most closely defining

the lane by using the least squares method on the points, then determining if the road modeling is completed; calculating a width of the lane if the road modeling is completed by calculating a camera parameter according to a positioning of the camera, and by determining a distance between pixels of image coordinates; and determining if the vehicle is veering from the lane using information of the width of the lane, and outputting a warning if it is determined that the vehicle is veering from the lane.

FIG. 1



EP 1 035 509 A1

**Description****BACKGROUND OF THE INVENTION****(a) Field of the Invention**

[0001] The present invention relates to a road modeling method for a lane drifting warning system, and more particularly to a method for a lane drifting warning system in which a road can be precisely modeled while a vehicle is being driven, even with the generation of errors caused by noise in road image signal data.

**(b) Description of the Related Art**

[0002] A conventional lane drifting warning system, with reference to FIG. 1, comprises a camera, such as a concatenated disk (CCD) camera for collecting images of lane markers and outputting corresponding image signals; an electronic control unit (ECU) for receiving the image signals output from the camera, processing the image signals using a pre-installed program to determine if the vehicle is veering from the lane it is in, and outputting alarm signals if it is determined that the vehicle is drifting out of the lane; and an alarm unit for outputting an alarm to alert the driver if the alarm signals are output from the ECU.

[0003] In such a conventional lane drifting warning system, road modeling is performed using the image signals and the program that is pre-installed in the ECU to determine if the vehicle is drifting out of the lane. The road modeling, with reference to FIG. 2a, is performed by extracting and selecting a plurality of points that are determined to be possible indications of road lane markers, then connecting the points by a straight line.

[0004] However, if noise is generated in the image signal data as a result of various external forces (e.g., radio wave interference, physical shocks given to the system, defective parts and operation of the system), road modeling errors can occur such that the lane marker modeling is distorted as shown in FIG. 2b. Accordingly, two serious outcomes may result: not warning the driver when the vehicle is veering from the lane, and erroneously outputting an alarm when the vehicle has not drifted out of the lane.

[0005] Further, complicated hardware is required to extract the points that are determined to be possible indications of road lane markers as described above. Finally, the process of extracting such points is inherently slow, making real-time operation difficult. This can lead to alerting the driver in an untimely manner.

**SUMMARY OF THE INVENTION**

[0006] The present invention has been made in an effort to solve the above problems.

[0007] It is an object of the present invention to provide a road modeling method for a lane drifting warning system in which after an edge of lane markers is extracted, road modeling is precisely performed even with the generation of errors as a result of noise in extracted lane marker data.

[0008] To achieve the above object, the present invention provides a road modeling method for a lane drifting warning system. The method includes the steps of extracting an edge of lane markers of a lane in which a vehicle is being driven by a camera collecting images of the lane markers and outputting corresponding image signals, removing noise from the lane marker image signals, and dividing the image signals into multiple resolutions; performing road modeling by inputting a minimum number of possible marking points of lane edges; and extracting two straight lines most closely defining the lane by using the least squares method on the points, then determining if the road modeling is completed; calculating a width of the lane if the road modeling is completed by calculating a camera parameter according to a positioning of the camera, and by determining a distance between pixels of image coordinates; and determining if the vehicle is veering from the lane using information of the width of the lane, and outputting a warning if it is determined that the vehicle is veering from the lane.

[0009] According to a feature of the present invention, the step of performing road modeling further includes the steps of inputting a minimum number of the possible marking points of the extracted lane edges; obtaining a linear function having a minimum deviation from the possible marking points of the lane edges; and obtaining lines of the lane markings defining the lane using the linear function.

**BRIEF DESCRIPTION OF THE DRAWINGS**

[0010] The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate an embodiment of the invention, and, together with the description, serve to explain the principles of the invention:

FIG. 1 is a block diagram of a conventional lane drifting warning system for vehicles;

FIG. 2a is a drawing used to illustrate modeling of lane markers in the conventional lane drifting warning system of FIG. 1;

FIG. 2b is a drawing used to illustrate modeling of lane markers in the conventional lane drifting warning system of FIG. 1, in which noise is generated in image signal data;

FIG. 3 is a flow chart of a road modeling method for a lane drifting warning system according to a preferred embodiment of the present invention;

FIG. 4 is a flow chart used to describe in more detail the road modeling method according to a preferred embodiment of the present invention; and

FIG. 5 is a graph used to illustrate road modeling using the least squares method according to a preferred embodiment of the present invention.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0011] Preferred embodiments of the present invention will now be described in detail with reference to the accompanying drawings.

[0012] FIG. 3 is a flow chart of a road modeling method for a lane drifting warning system according to a preferred embodiment of the present invention.

[0013] First, in step S20, a camera collects images of lane markers of a lane in which the vehicle is being driven, then the images are converted into image signals and output. Next, noise is removed from the lane marker images in step S21, after which the images are divided into multiple resolutions in step S22. Subsequently, while maintaining the multiple resolutions, lane marker edges are quickly extracted in step S23. After the lane marker edges are extracted in step S23, road modeling is performed in step S24. That is, a minimum number of possible markings of lane edges are input, then a straight line most closely following the markings is extracted by using the least squares method (i.e., "the least squares fit").

[0014] Next, it is determined if the road modeling process is completed in step S25. If the road modeling is not completed in step S25, the process returns to step S23. However, if the road modeling is completed in step S25, a camera parameter according to a positioning of the camera is calculated, and a width of the lane according to a distance between pixels of image coordinates is determined in step S26. After this step, it is determined if the vehicle is veering from the lane in step S27. If the vehicle is not veering from the lane in step S27, the process returns to step S23. However, if the vehicle is drifting out of the lane in step S27, a warning is output to alert the driver in step S28.

[0015] FIG. 4 is a flow chart used to describe in more detail the road modeling method according to a preferred embodiment of the present invention. First, a minimum number of possible markings of the extracted lane edges are input in step S40. Next, a linear function having a minimum deviation is obtained from the possible markings of the lane edges by using the least squares method in step S41. Following this step, lines defining the lane markings are obtained using the linear function in step S42, thereby completing the road modeling process.

[0016] FIG. 5 is a graph used to illustrate road modeling using the least squares method according to a preferred embodiment of the present invention. As shown in the drawing, a compromise line fit of the line marking data is obtained using the least squares method, or "least squares fit". That is, after a plurality of possible points for the lane markers are obtained, the least squares method is used to find a compromise line that follows the flow of the points.

[0017] The operation of the above method of the present invention will be described hereinafter with reference to elements of a lane drifting warning system.

[0018] A CCD camera is mounted at a predetermined location on the vehicle and the camera is connected to an electronic control unit (ECU), the ECU having a predetermined program installed therein. When the vehicle is operated, the camera collects images of lane markers and outputs corresponding image signals to the ECU, thereby performing step S20 in which image signals are input to the ECU.

[0019] Next, step S21 is performed in which noise is removed from the image signals using a median filter. After this operation, step S22 is performed in which the image signals are divided into multiple resolutions, thereby enabling the image signals to be quickly processed. That is, the number of pixels in the image signals input into the ECU is reduced in the same, and the pixels are divided to have different multiple resolutions.

[0020] Following the above, the ECU performs step S23 and extracts lane marker edges from the lane marker image signals which are divided having different resolutions. Next, the ECU conducts step S24 in which road modeling is performed. In more detail, with reference to FIG. 4, a minimum number of possible markings of the extracted lane edges are input in step S40. Next, performing step S41, a linear function having a minimum deviation is obtained from the possible markings of the lane edges by using the least squares method. Finally, in step S42, lines defining the lane markings are obtained using the linear function in step S42, thereby completing the road modeling process. The following outlines the development of equations to perform this operation.

$$y(x) = a + b x, \text{ b: unknown quantity} \quad (1)$$

[0021] To obtain a deviation ( $r_i$ ) of each point in equation (1),

$$r_i = y_i - y(x) = y_i - (a + b x_i), \text{ i = 1, 2, 3, iL: total number of measured coordinates} \quad (2)$$

[0022] A total (R) of the squares of deviations

$$R = \sum (r_i)^2 = \sum (y_i - a - b x_i)^2 \quad (3)$$

a value to minimize the value of R is obtained

[0023] The differentiation of R with respect to a and b is set to 0.

$$\text{differentiation } (R/a) = -2 \sum (y_i - a - b x_i) = 0$$

$$\text{differentiation } (R/b) = -2 \sum (x_i - a - b x_i) = 0 \quad (4)$$

[0024] If equation (4) is written matrix form:

$$(A(1,1) \ A(1,2), A(2,1) \ A(2,2)) (a, b) = (Z1, Z2) \quad (5)$$

with:

$$\begin{aligned} A(1,1) &= L \\ A(1,1) &= \sum x_i \\ Z1 &= \sum y_i \\ A(1,1) &= \sum x_i \\ A(1,1) &= \sum (x_i)^2 \\ Z1 &= \sum x_i y_i \\ a \text{ and } b &\text{ are:} \end{aligned}$$

$$a = [A(2,2)Z1 - A(1,2)Z2] / d$$

$$b = [A(1,1)A(2,2) - A(1,2)A(2,1)] / d \quad (6)$$

$$d = A(1,1) A(2,2) - A(1,2) A(2,1): \text{determined}$$

[0025] An outline of measured lane marker points is as follows:

Table 1

i	X	v
1	0.1	0.61
2	0.4	0.92
3	0.5	0.99
4	0.7	1.52
5	0.7	1.47
6	0.9	2.03

[0026] As shown by the measured values in Table 1, also appearing in FIG. 5, even though possible lane markings (i) 2 and 3 are obvious errors resulting from noise, the straight line made following the flow of possible lane markings (i) 1, 4, 5 and 6 compensates for these errors.

[0027] After the ECU has performed the process of road modeling of step S24 as in the above, the ECU performs step S25 and determines if the road modeling is completed. If it is determined that road modeling is not completed, the process returns to step S23. However, if the road modeling is completed, the ECU performs step S26 in which a camera parameter is obtained for fixing the camera at an initial position and calculating the actual width of the lane in order to extract the actual width of the lane from two-dimensional image coordinates with regard to the image signals input from the CCD camera. After the camera parameter is obtained, the actual width of the lane, in the road modeled as in the above, is calculated according to a distance between pixels of image coordinates.

[0028] Following the above, the ECU performs step S27 in which it is determined if the vehicle is veering out of the width of the lane calculated in step S26. At this time, if it is determined by the ECU that the vehicle is not veering from the lane, the process returns to step S23. However, if the vehicle is drifting out of the lane in step S27, the ECU performs step S28 and outputs alarm-out signals to an alarm unit, which in turn outputs a warning to alert the driver.

[0029] In the road modeling method for a lane drifting warning system of the present invention as described above, precise road modeling of a lane the vehicle is driving in is possible, even with the generation of errors caused by noise in road image signal data.

[0030] Although preferred embodiments of the present invention have been described in detail hereinabove, it should be clearly understood that many variations and/or modifications of the basic inventive concepts herein taught which may appear to those skilled in the present art will still fall within the spirit and scope of the present invention, as defined in the appended claims.

## Claims

1. A road modeling method for a lane drifting system comprising the steps of:

extracting an edge of lane markers of a lane in which a vehicle is being driven by a camera collecting images of the lane markers and outputting corresponding image signals, removing noise from the lane marker image signals, and dividing the image signals into multiple resolutions;

performing road modeling by inputting a minimum number of possible marking points of lane edges, and extracting two straight lines most closely defining the lane by using the least squares method on the points, then determining if the road modeling is completed;

calculating a width of the lane if the road modeling is completed by calculating a camera parameter according to a positioning of the camera, and by determining a distance between pixels of image coordinates; and determining if the vehicle is veering from the lane using information of the width of the lane, and outputting a warning if it is determined that the vehicle is veering from the lane.

2. The road modeling method of claim 1 wherein the step of performing road modeling further comprises the steps of:

inputting a minimum number of the possible marking points of the extracted lane edges;

obtaining a linear function having a minimum deviation from the possible marking points of the lane edges; and

obtaining lines of the lane markings defining the lane using the linear function.

FIG. 1




FIG. 3




FIG. 2a




FIG. 2b






FIG. 5



*FIG. 4*





European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 99 12 5092

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 301 115 A (NOUSO KAZUNORI) 5 April 1994 (1994-04-05) * abstract * * column 1, line 41 - line 60 * * column 14, line 43 - line 50 *	1,2	G06T7/00 G06T5/00
A	EP 0 586 857 A (ROCKWELL INTERNATIONAL CORP) 16 March 1994 (1994-03-16) * abstract * * column 4, line 35 - line 44 *	1,2	
A	EP 0 527 665 A (MATRA SEP IMAGERIE ET INF SOCI) 17 February 1993 (1993-02-17) * abstract * * column 1, line 23 - line 33 * * column 3, line 30 - line 48 *	1,2	
A	EP 0 488 828 A (HONDA MOTOR CO LTD) 3 June 1992 (1992-06-03) * abstract * * page 19, line 17 - line 28 *	1,2	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			G06T
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>11 July 2000</b>	Examiner <b>Gonzalez Ordenez, O</b>
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 (03.02.92) (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 12 5092

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

11-07-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5301115 A	05-04-1994	JP 2754871 B	20-05-1998
		JP 4036878 A	06-02-1992
EP 0586857 A	16-03-1994	US 5351044 A	27-09-1994
		CA 2090660 A	13-02-1994
		DE 69302975 D	11-07-1996
		DE 69302975 T	19-12-1996
		JP 6109433 A	19-04-1994
EP 0527665 A	17-02-1993	FR 2679357 A	22-01-1993
		DE 69204239 D	28-09-1995
		DE 69204239 T	25-01-1996
		ES 2076712 T	01-11-1995
EP 0488828 A	03-06-1992	JP 4205320 A	27-07-1992
		JP 2836949 B	14-12-1998
		JP 4205321 A	27-07-1992
		DE 69121369 D	19-09-1996
		DE 69121369 T	09-01-1997
		US 5307419 A	26-04-1994

EPO FORM P2459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82